

Unmanned Aerial Systems Traffic Management (UTM)


Technology Capability Level Field Demonstrations

NASA

http://www.utm.arc.nasa.gov

Moffett Field, CA

Parimal Kopardekar, Joseph Rios, Marcus Johnson,
Jaewoo Jung and Tom Prevot



Field Demonstration Objectives

TCL 1: August 2015

Line of Sight Operations
Low Risk Environment
Airspace Reservation
Geo-fencing for Separation
No Fly Zones
User Authentication

TCL 2: October 2016

Beyond Line of Sight Operations
Low Risk Environment
Segmented Flight Plans
Weather and Traffic Advisories
Altitude Stratification
Contingency Management (Alerting)
System Health Monitoring



TCL 1 UAS Operations

MEM Tower Inspection Wind Turbi Inspection Power Line Inspection Wind Turbine **Bridge Inspection**

Solar Panel Inspection

Power Line

Rail Inspection

Landfill Inspection

Pipeline Inspection Dam Inspection

Canal Inspection

Aerial Application
Precision
Agriculture

Livestock Monitoring

Invasive Plant Monitoring

Forest

Management

Mosquito Monitoring

Wildlife Conservation

Archaeology

Anthropology

Prospecting

Maritime

Surveillance

Maritime Scouting

Ocean Research **Anti-Piracy**


eation **Animal Spotting for** Hunting Nature

Photography


Adventure Sports **Photography**

<u>Typical Operation Limitations</u>

Line of Sight Operations **Sparsely Populated Areas** Typically <400 ft AGL VMC Conditions & Daylight **UAS** < 55lbs 500 ft away from structures








Demonstration Objectives


Objective 5: Collect Data on Noise Signature of UAS Vehicles



Objective 2: Collect Data on UAS Navigation Performance Error

Objective 3: Collect Data on Aircraft Tracking Performance






Objective 4: Collect Weather Observations for Forecasting Models

UTM Vehicles







UTM Manager Displays







Java-based Desktop Display

iOS Application

UTM Field Equipment : Weather

32m Weather Tower





Radiosonde Weather Balloon

Data Collected

Temperature
Pressure
Wind Direction
Wind Speed
Altitude
Turbulent Kinetic Energy

Remote Automated Weather Station



UTM Field Equipment : Surveillance and Acoustics

Short Range Radar








Data Collected


Latitude
Longitude
Altitude
Sound magnitude and
frequency

Acoustic Measurement












Ground Situation Awareness
Display (ADS-B In, En Route
radar, Terminal Radar, ASDEX, ASSC)



Observations of Operational Use

- New Airspace Users will require training and UTM needs to be intuitive
 - Observation: UAS Operators submitting an operational plan to the system that differs from what was input into the GCS or a willingness to violate an operational plan.
 - Recommendation: Operator training and integration of flight planning and traffic management services into ground control stations
- The right equipment for the operational environment
 - Observation: High temperatures had impact on ground equipment. C2 interference occurred with local farming equipment. Degradation of GPS signals impacted flight operations.
 - Recommendation: UAS and ground systems and instruments are "qualified" by operational environment and performance.
- Situation awareness is key for safe operations
 - Observation: sUAS varies with size and line of sight (LOS) can be easily lost (e.g. sUAS looked like birds during operation). Weather reported on the ground isnt always indicative of weather experienced at operational altitude. Tracking of sUAS needs to occur at sufficiently fast update rates.
 - Recommendation: Improvements are needed in weather forecasting, modeling, and sensing at low altitudes. Tracking UAS infrastructure will need to be built to scale and with sufficient bandwidth. Airspace users should be given a common picture of their environment for safe operations.



TCL 2 Demonstration Characteristics


Flight Operations:

- Operate 5 simultaneous operations
- Operate two aircraft beyond visual line of sight (BVLOS)
- Operate two aircraft in an altitude separated operation in visual line of sight (VLOS)
- Operate two aircraft in an altitude-separated operation in BVLOS
- Demonstrate Live-Virtual-Constructive Operations

UTM Functionality:

- Alerting UAS operators of threat aircraft based on data from surveillance system
- Monitoring UAS operations for flight plan conformance
- Alerting UAS Operators due to weather disruption
- Alerting and contingency management procedures initiated by simulated in-flight emergencies of UAS operations
- Dynamic requested flight plan rerouting
- Public safety operations

TCL 2 Demonstration: Reno-Stead Airport



Dates: Oct. 17th -26th

Reno-Stead Airport:

- Part of UAS Test Site
- Public and military general aviation airport located 10 nautical miles northwest of Reno, Nevada.
- Location of the Reno Air Races
- Elevation: 5050 ft (AMSL)

14+ Partners:

- BVLOS Vehicles
- Surveillance and Weather Equipment

